

DesCase non-desiccant Breathers



Prevent Contamination, Safeguard Health of Employees & Machines

Rotating equipment, such as gearboxes, typically generates large amounts of oil mist and vaporized oil, thus contaminating ambient air surrounding machines.

Non-desiccant breather benefits:

- Creates an impenetrable barrier against water droplets
- Pleated element provides a large surface area and is 99.5% efficient in blocking particles 1 micron or larger
- Coalesces oil mist, preventing contamination of working environment (TriplePlay only)
- Visual vacuum indicator option actuates when maximum restriction is reached
- Rugged ABS plastic housing
- Easy installation requires hand tighten only

Models, Accessories & Installation Methods

The Des-Case TriplePlay™ nondesiccant breathers incorporate a 1" NPT threaded mounting design for easy adaptation to any size reservoir opening with adapter or reducer options.

Nondesiccant Breathers

Model #	Diameter	Height	Water Adsorption	Flow Rate	Connection Size
DC-SB-25	5" / 12.7 cm	5" / 12.7 cm	n/a	40 cfm	1" NPT

TekTrade Baltic OÜ
Reg no. 11228551
VAT no. EE101053370

Postal Address:
Lauri tee 33-2
11912 Tallinn Estonia
Office & Storehouse:
Veerenni 56A,
11313 Tallinn Estonia

Tel. +3726546610
Mob +3725040732
Fax +3726091399
tektrade@tektrade.ee
www.tektrade.ee

IBAN EE741700017000948566

Nordea Bank Finland Plc /
Estonia Branch
S.W.I.F.T. address: NDEAFIHH
in favour of NDEAEE2X