

## Technical Datasheet

### **BRAIDED E-GLASS FIBRE SLEEVING - 550°C**

Sleeving is produced by braiding several types of yarn into a circular tube.

**Braided E-Glass sleeving** is a flexible HT tubular textile product for the protection and the insulation of hoses, pipes, cables or wires. Keramab N.V. has in-house facilities to apply the protective braiding directly on the flexible products.

**Braided E-Glass sleeving** is made from texturized, continuous E-Glass fibre filaments up to a maximum of 9 microns. These fibres cause considerably less irritation of the skin than the coarser fibres.

#### Chemical Properties

**Braided E-Glass sleeving** exhibits excellent chemical stability resisting attack from most corrosive agents. Exceptions are hydrofluoric acids and phosphoric acids and concentrated alkalis. No water of hydration is present. Excellent die-electrical strength.

#### Availability

**Braided E-Glass sleeving** is available in the following diameter sizes : 8-60 mm. Other sizes available on request.

#### Applications

- Cable and wire insulation (thermal and/or electrical)
- Fuel line insulation
- Pipe hanger insulation
- Thermal insulation of steam-pipes in wells
- Wrapping of exhausts

#### Typical Physical Properties

Average density	200 - 600 kg/m <sup>3</sup>
Colour	White
Basic Composition	Silica
Continuous Use Limit	550°C
Melting Point	840°C

Form: A3-060  
Effective: 25081997.WVDS.mvo  
Supersedes: SS.None  
All Rights Reserved

Price schedule : K-3800

The information, recommendations and opinions set forth herein are offered solely for your consideration, inquiry and verification, and are not, in part or total, to be construed as constituting a warranty or representation for which we assume legal responsibility. Nothing contained herein is to be interpreted as authorization to practice a patented invention without a license.

Page 1 of 1

**The Netherlands – Insulcon B.V.**  
Tel: +31(0)167-565750  
Fax: +31(0)167-566263



**Belgium – Keramab N.V.**  
Tel: +32(0)3 711 02 78  
Fax: +32(0)3 711 08 56



**Germany – Insulcon GmbH**  
Tel: +49(0)2162/ 24960-0  
Fax: +49(0)2162/24960-29

